



SAFETY DATA SHEET

1. Identification

Product identifier	Gasket Remover - 12 oz
Other means of identification	
Product Code	No. 05021 (Item# 1003638)
Recommended use	Gasket remover
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)
Website	crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Do not breathe mist/vapors. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Response

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	45 - 55
liquefied petroleum gas		68476-86-8	20 - 30
1-methylpyrrolidin-2-one		872-50-4	15 - 25
xylene		1330-20-7	1 - 3
cocamide DEA		68603-42-9	0.1 - 1
ethylbenzene		100-41-4	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
ethylbenzene (CAS 100-41-4)	PEL	435 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
		100 ppm
xylene (CAS 1330-20-7)	PEL	435 mg/m3
		100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
ethylbenzene (CAS 100-41-4)	TWA	20 ppm
xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
xylene (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1-methylpyrrolidin-2-one (CAS 872-50-4)	STEL	120 mg/m3
		30 ppm
	TWA	60 mg/m3
		15 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
1-methylpyrrolidin-2-one (CAS 872-50-4)	100 mg/l	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	*
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

1-methylpyrrolidin-2-one (CAS 872-50-4)

Can be absorbed through the skin.

US WEEL Guides: Skin designation

1-methylpyrrolidin-2-one (CAS 872-50-4)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Butyl rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol.

Color

Colorless.

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-139.6 °F (-95.4 °C) estimated

Initial boiling point and boiling range

132.8 °F (56 °C) estimated

Flash point

-4.0 °F (-20.0 °C) estimated

Evaporation rate

Fast.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1 % estimated

Explosive limit - upper (%) 14.3 % estimated

Vapor pressure

1387.8 hPa estimated

Vapor density

> 1 (air = 1)

Relative density

0.78 estimated

Solubility(ies)

Solubility (water)

Soluble.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

473 °F (245 °C) estimated

Decomposition temperature

Not available.

Viscosity

166 cP

Percent volatile

67 % estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens. Peroxides. Phenols.
Hazardous decomposition products	Aldehydes. Carbon oxides. Hydrocarbon fumes and smoke. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Product	Species	Test Results
Gasket Remover - 12 oz		
Acute		
Dermal		
ATEmix		21795.2 mg/kg bw
Oral		
ATEmix		5559.08 mg/kg bw

Components	Species	Test Results
1-methylpyrrolidin-2-one (CAS 872-50-4)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg 8000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50		> 20 mg/l
Oral		
LD50	Rat	3600 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

cocamide DEA (CAS 68603-42-9)	2B Possibly carcinogenic to humans.
ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	Toxic to aquatic life.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
1-methylpyrrolidin-2-one	-0.38
acetone	-0.24
ethylbenzene	3.15
Bioconcentration factor (BCF)	
ethylbenzene	1
xylene	23.99
Mobility in soil	No data available.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	This material and its container must be disposed of as hazardous waste. Empty container can be recycled. Full or partially-full aerosol cans can be treated as universal waste. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of this material and its container to hazardous or special waste collection point. Dispose in accordance with all applicable regulations.
Hazardous waste code	Possible RCRA waste code includes: D001: Waste Flammable material with a flash point <140 F F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.


14. Transport information

DOT


UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not assigned.
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None

Packaging bulk	None
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



IATA



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

- acetone (CAS 67-64-1)
- ethylbenzene (CAS 100-41-4)
- xylene (CAS 1330-20-7)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1)	5000 LBS
ethylbenzene (CAS 100-41-4)	1000 LBS
xylene (CAS 1330-20-7)	100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

1-methylpyrrolidin-2-one (CAS 872-50-4)	1.0 % Annual Export Notification required.
---	--

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ethylbenzene (CAS 100-41-4)
xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

acetone (CAS 67-64-1)	6532
-----------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1)	35 %WV
-----------------------	--------

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1)	6532
-----------------------	------

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1)	Low priority
-----------------------	--------------

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids)
	Gas under pressure
	Skin corrosion or irritation
	Serious eye damage or eye irritation
	Carcinogenicity
	Reproductive toxicity
	Specific target organ toxicity (single or repeated exposure)
	Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1-methylpyrrolidin-2-one	872-50-4	15 - 25
ethylbenzene	100-41-4	0.1 - 1
xylene	1330-20-7	1 - 3

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1-methylpyrrolidin-2-one (CAS 872-50-4)
acetone (CAS 67-64-1)
cocamide DEA (CAS 68603-42-9)
ethylbenzene (CAS 100-41-4)
xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1-methylpyrrolidin-2-one (CAS 872-50-4)
acetone (CAS 67-64-1)
ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

1-methylpyrrolidin-2-one (CAS 872-50-4)

acetone (CAS 67-64-1)

ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-methylpyrrolidin-2-one (CAS 872-50-4)

acetone (CAS 67-64-1)

ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

US. Rhode Island RTK

acetone (CAS 67-64-1)

ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0)

Listed: April 1, 1988

benzene (CAS 71-43-2)

Listed: February 27, 1987

cocamide DEA (CAS 68603-42-9)

Listed: June 22, 2012

cumene (CAS 98-82-8)

Listed: April 6, 2010

diethanolamine (CAS 111-42-2)

Listed: June 22, 2012

ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

naphthalene (CAS 91-20-3)

Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

1-methylpyrrolidin-2-one (CAS 872-50-4)

Listed: June 15, 2001

benzene (CAS 71-43-2)

Listed: December 26, 1997

mercury (CAS 7439-97-6)

Listed: July 1, 1990

methanol (CAS 67-56-1)

Listed: March 16, 2012

toluene (CAS 108-88-3)

Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)

Listed: December 26, 1997

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) 47.8 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products This product is regulated as a Gasket Adhesive Remover. This product is compliant for use in all 50 states.

VOC content (CA) 47.4 %

VOC content (OTC) 47.4 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-25-2023
Prepared by	Joshua Weir
Version #	01
Further information	CRC # 1754538
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..
Revision information	This document has undergone significant changes and should be reviewed in its entirety.