

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

Other means of identification

No. 05063 (Item# 1003679) **Product Code** 

**Product registration** 

number

048320032

EPA: 048320032 Registration number Recommended use Fuel system additive

None known. Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name

**Address** 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

215-674-4300 **General Information** 800-521-3168 **Technical Assistance Customer Service** 800-272-4620 800-424-9300 (US) 24-Hour Emergency

(CHEMTREC)

Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Flammable liquids Category 4 **Health hazards** Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2 Germ cell mutagenicity Category 2

Carcinogenicity Category 2 Aspiration hazard Category 1 Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

**OSHA** defined hazards Not classified.

Label elements

**Environmental hazards** 



Signal word Danger

**Hazard statement** Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful if

inhaled. Suspected of causing genetic defects. Suspected of causing cancer.

**Precautionary statement** 

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces. - No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing vapors. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Category 2

Material name: Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the

fire

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrodesulfurized middle	Diesel Fuel No. 2	64742-80-9	80 - 90
solvent naphtha (petroleum), ligh arom.	t	64742-95-6	5 - 10
1,2,4-trimethylbenzene		95-63-6	1 - 5
polyolefin alkyl phenol alkyl amin	e	Proprietary	1 - 5
cumene		98-82-8	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

mixtures. During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighte Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

(CAS 64742-80-9)

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
cumene (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	PEL	400 mg/m3	
		100 ppm	
solvent naphtha (petroleum), light arom. (CAS 64742-95-6)	PEL	400 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Values	<b>S</b>		
Components	Туре	Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
cumene (CAS 98-82-8)	TWA	50 ppm	
distillates (petroleum), hydrodesulfurized middle	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Che Components	mical Hazards Type	Value	
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
cumene (CAS 98-82-8)	TWA	245 mg/m3	
		50 ppm	
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	TWA	400 mg/m3	
		100 ppm	
solvent naphtha (petroleum), light arom. (CAS 64742-95-6)	TWA	400 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US - California OELs: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

100 ppm

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl chloride (PVC).

**Other** Wear appropriate chemical resistant clothing.

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.
Color Light yellow.
Odor Petroleum.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -46.8 °F (-43.8 °C) estimated Initial boiling point and boiling 311 °F (155 °C) estimated

range

Flash point 175.0 °F (79.4 °C) Setaflash

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 0.6 % estimated

(%)

(%)

Flammability limit - upper

7.5 % estimated

Vapor pressure 0.7 hPa estimated

Vapor density > 1 (air = 1)
Relative density 0.82

Relative density

Solubility(ies)

Solubility (water) Negligible.

Partition coefficient Not available.

(n-octanol/water)
Auto-ignition temperature

494 °F (256.7 °C) estimated

Decomposition temperature Not available.

Percent volatile 83.7 % estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials
Hazardous decomposition

products

Strong oxidizing agents.
Carbon oxides. Aldehydes.

# 11. Toxicological information

Information on likely routes of exposure

InhalationHarmful if inhaled.Skin contactCauses skin irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Skin irritation. May cause

redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Product Species Test Results

Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

<u>Acute</u> Oral

ATEmix 31022.980125195027 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Material name: Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

No. 05063 (Item# 1003679) Version #: 06 Revision date: 07-17-2020 Issue date: 04-11-2019

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity Suspected of causing genetic defects.

**Carcinogenicity** Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

cumene (CAS 98-82-8) 2B Possibly carcinogenic to humans.

solvent naphtha (petroleum), light arom. 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-95-6)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

cumene (CAS 98-82-8) Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity**Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

cumene 3.66 distillates (petroleum), hydrodesulfurized middle 3.3 - 6

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

cumene (CAS 98-82-8)

**CERCLA Hazardous Substances: Reportable quantity** 

cumene (CAS 98-82-8)

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

cumene (CAS 98-82-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-trimethylbenzene	95-63-6	1 - 5
cumene	98-82-8	< 0.2

## **US** state regulations

### US. New Jersey Worker and Community Right-to-Know Act

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

solvent naphtha (petroleum), light arom. (CAS 64742-95-6)

# US. Massachusetts RTK - Substance List

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

solvent naphtha (petroleum), light arom. (CAS 64742-95-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

solvent naphtha (petroleum), light arom. (CAS 64742-95-6)

## **US. Rhode Island RTK**

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

solvent naphtha (petroleum), light arom. (CAS 64742-95-6)

## **California Proposition 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0) Listed: April 1, 1988

 benzene (CAS 71-43-2)
 Listed: February 27, 1987

 cumene (CAS 98-82-8)
 Listed: April 6, 2010

 furan (CAS 110-00-9)
 Listed: October 1, 1993

 naphthalene (CAS 91-20-3)
 Listed: April 19, 2002

 propylene oxide (CAS 75-56-9)
 Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-trimethylbenzene (CAS 95-63-6)

cumene (CAS 98-82-8)

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9) solvent naphtha (petroleum), light arom. (CAS 64742-95-6)

### Volatile organic compounds (VOC) regulations

#### **EPA**

**VOC content (40 CFR** > 97.5 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products Not regulated VOC content (CA) 89.8 % VOC content (OTC) 89.8 %

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

# 16. Other information, including date of preparation or last revision

Issue date04-11-2019Revision date07-17-2020Prepared byAllison Yoon

Version # 06

Further information CRC # 1752118

**Disclaimer**The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Material name: Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision information	This document has undergone significant changes and should be reviewed in its entirety.

Material name: Guaranteed To Pass® Emissions System Cleaner - 12 fl oz

No. 05063 (Item# 1003679) Version #: 06 Revision date: 07-17-2020 Issue date: 04-11-2019