### SAFETY DATA SHEET

#### 1. Identification

**Product identifier** Engine Tune-Up & Decarbonizer - 13 oz

Other means of identification

No. 06121 (Item# 1003919) **Product Code** Recommended use Engine tune-up and decarbonizer

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name 885 Louis Dr. **Address** 

Warminster, PA 18974 US

**Telephone** 

**General Information** 215-674-4300 **Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

### 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Gases under pressure Liquefied gas Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

**OSHA** defined hazards Not classified.

Label elements

**Health hazards** 



Signal word Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if **Hazard statement** 

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful to

aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement** Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear eye protection/face protection. Wear protective gloves. Wash thoroughly after handling. Avoid release to the environment.

SDS US 1 / 11 No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

**Storage** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### **Mixtures**

ne and synonyms CAS number	<u></u>
64742-52-5	50 - 60
68476-86-8	20 - 30
111-76-2	5 - 10
123-42-2	3 - 5
95-63-6	1 - 3
91-57-6	1 - 3
577-11-7	1 - 3
90-12-0	< 1
	64742-52-5 68476-86-8 111-76-2 123-42-2 95-63-6 91-57-6 577-11-7

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

illeula

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

equipment/instructions
General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

·

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place.

### 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Туре	Value	Form
PEL	240 mg/m3	
	50 ppm	
PEL	240 mg/m3	
	50 ppm	
PEL	5 mg/m3	Mist.
	2000 mg/m3	
	500 ppm	
Туре	Value	Form
TWA	25 ppm	
TWA	0.5 ppm	
TWA	20 ppm	
	PEL PEL  PEL  Type  TWA  TWA	PEL 240 mg/m3 50 ppm 240 mg/m3  50 ppm 50 ppm 5 mg/m3  2000 mg/m3 500 ppm  Type Value  TWA 25 ppm  TWA 0.5 ppm

Material name: Engine Tune-Up & Decarbonizer - 13 oz

No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019 3 / 11

Components		Type			Value	Form
2-methylnaphthalene (CAS 91-57-6)		TWA			0.5 ppm	
4-hydroxy-4-methylpentan-2 -one (diacetone alcohol) (CAS 123-42-2)	2	TWA			50 ppm	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		TWA			5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide	to Chemical Ha	zards				
Components		Type			Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)		TWA			125 mg/m3	
					25 ppm	
2-butoxyethanol (CAS 111-76-2)		TWA			24 mg/m3	
					5 ppm	
4-hydroxy-4-methylpentan-2 -one (diacetone alcohol) (CAS 123-42-2)	2	TWA			240 mg/m3	
(6.12.12.12.1)					50 ppm	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		Ceilin	9		1800 mg/m3	
· · · · · · · · · · · · · · · · · · ·		STEL			10 mg/m3	Mist.
		TWA			5 mg/m3	Mist.
ogical limit values						
ACGIH Biological Exposu	re Indices					
Components	Value		Determinant	Specimen	Sampling	Time
2-butoxyethanol (CAS 111-76-2)	200 mg/g		Butoxyacetic acid (BAA), with hydrolysis	Creatinine urine	in *	
2-methylnaphthalene (CAS 91-57-6)	2.5 µg/l		1-Hydroxypyre ne, with hydrolysis (1-HP)	Urine	*	
* - For sampling details, plea	ase see the sour	ce docu	ment.			
osure guidelines						
US - California OELs: Skir	-					
2-butoxyethanol (CAS of US - Minnesota Haz Subs:		n appli		absorbed the	ough the skin.	
2-butoxyethanol (CAS US - Tennessee OELs: Sk	in designation			esignation app		
2-butoxyethanol (CAS OUS ACGIH Threshold Limit		esigna		absorbed the	ough the skin.	
1-methylnaphthalene (0 2-methylnaphthalene (0					ough the skin. ough the skin.	

Can be absorbed through the skin.

2-butoxyethanol (CAS 111-76-2)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

### Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene. Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. **Form** Aerosol. Color Amber. Odor Camphor. Not available. Odor threshold Not available. pН

Melting point/freezing point -102.6 °F (-74.8 °C) estimated Initial boiling point and boiling 212 °F (100 °C) estimated

range

Flash point 154 °F (67.8 °C) Setaflash

**Evaporation rate** Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

12.6 % estimated

(%)

982.3 hPa estimated Vapor pressure

> 1 (air = 1)Vapor density Relative density 0.84 estimated

Solubility(ies)

Negligible. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

460.4 °F (238 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. Viscosity Not available. 92 % estimated Percent volatile

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Material name: Engine Tune-Up & Decarbonizer - 13 oz

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials

Hazardous decomposition

products

Strong oxidizing agents.

Carbon oxides.

### 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness

and pain.

#### Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results	
2-butoxyethanol (CAS 111	1-76-2)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	220 mg/kg	
Oral			
LD50	Rat	470 mg/kg	
4-hydroxy-4-methylpentan	-2-one (diacetone alcohol) (CAS 123-42-2)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	13500 mg/kg	
distillates (petroleum), hyd	rotreated heavy naphthenic (CAS 64742-52-5)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Oral			
LD50	Rat	> 5000 mg/kg	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

#### IARC Monographs. Overall Evaluation of Carcinogenicity

No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019

2-butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Material name: Engine Tune-Up & Decarbonizer - 13 oz

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting,

may cause chemical pneumonia, pulmonary injury or death.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

### 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1,2,4-trimethylbenzen	e (CAS 95-63-6)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	3.6 mg/l, 48 hours
1-methylnaphthalene	(CAS 90-12-0)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	9 mg/l, 96 hours
2-butoxyethanol (CAS	111-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
2-methylnaphthalene	(CAS 91-57-6)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.07 - 1.841 mg/l, 96 hours
4-hydroxy-4-methylpe	ntan-2-one (diaceto	ne alcohol) (CAS 123-42-2)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8750 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	420 mg/l, 96 hours
		Goldfish (Carassius auratus)	> 5000 mg/l, 24 hours
dioctyl sodium sulfosu	ccinate (CAS 577-1	11-7)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	20 - 40 mg/l, 96 hours
distillates (petroleum),	hydrotreated heav	y naphthenic (CAS 64742-52-5)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1000 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours
Crustacea		Rainbow trout,donaldson trout	<b>3</b> /

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product. **Bioaccumulative potential** 

\_\_\_\_\_

No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019

Partition coefficient n-octanol / water (log Kow)

3.87 1-methylnaphthalene 2-butoxyethanol 0.83 2-methylnaphthalene 3.86 4-hydroxy-4-methylpentan-2-one (diacetone alcohol) -0.098

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). **Disposal instructions** 

> Empty container can be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in

accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. Transport information

DOT

UN1950 **UN** number

**UN** proper shipping name

Transport hazard class(es)

Aerosols, flammable, Limited Quantity

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions Packaging non bulk 304 Packaging bulk None

IATA

**UN** number UN1950

**UN** proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not applicable. Packing group

**ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Allowed with restrictions.

Cargo aircraft only

**IMDG** 

**UN** number UN1950

**UN** proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not applicable. Packing group

**Environmental hazards** 


Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Engine Tune-Up & Decarbonizer - 13 oz

No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019

### DOT; IMDG



### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-trimethylbenzene (CAS 95-63-6)

2-butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

2-butoxyethanol (CAS 111-76-2)

**CERCLA Hazardous Substances: Reportable quantity** 

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-methylnaphthalene (CAS 91-57-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure Skin corrosion or irritation

Serious eye damage or eye irritation

Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-trimethylbenzene	95-63-6	1 - 3	
2-butoxyethanol	111-76-2	5 - 10	

#### **US state regulations**

#### US. New Jersey Worker and Community Right-to-Know Act

1,2,4-trimethylbenzene (CAS 95-63-6)

1-methylnaphthalene (CAS 90-12-0)

2-butoxyethanol (CAS 111-76-2)

2-methylnaphthalene (CAS 91-57-6)

4-hydroxy-4-methylpentan-2-one (diacetone alcohol) (CAS 123-42-2)

#### **US. Massachusetts RTK - Substance List**

1,2,4-trimethylbenzene (CAS 95-63-6)

1-methylnaphthalene (CAS 90-12-0)

2-butoxyethanol (CAS 111-76-2)

4-hydroxy-4-methylpentan-2-one (diacetone alcohol) (CAS 123-42-2)

#### US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-trimethylbenzene (CAS 95-63-6)

1-methylnaphthalene (CAS 90-12-0)

2-butoxyethanol (CAS 111-76-2)

4-hydroxy-4-methylpentan-2-one (diacetone alcohol) (CAS 123-42-2)

#### **US. Rhode Island RTK**

1,2,4-trimethylbenzene (CAS 95-63-6)

4-hydroxy-4-methylpentan-2-one (diacetone alcohol) (CAS 123-42-2) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

#### **California Proposition 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

 1,4-dioxane (CAS 123-91-1)
 Listed: January 1, 1988

 benzene (CAS 71-43-2)
 Listed: February 27, 1987

 cumene (CAS 98-82-8)
 Listed: April 6, 2010

 ethylene oxide (CAS 75-21-8)
 Listed: July 1, 1987

 naphthalene (CAS 91-20-3)
 Listed: April 19, 2002

### California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

#### California Proposition 65 - CRT: Listed date/Female reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

#### California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)

ethylene oxide (CAS 75-21-8)

Listed: December 26, 1997

Listed: August 7, 2009

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-trimethylbenzene (CAS 95-63-6)

1-methylnaphthalene (CAS 90-12-0)

2-butoxyethanol (CAS 111-76-2)

2-methylnaphthalene (CAS 91-57-6)

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

### Volatile organic compounds (VOC) regulations

### **EPA**

**VOC content (40 CFR** 97.9 %

51.100(s))

Consumer products Compliant

(40 CFR 59, Subpt. C)

SDS US

State

Consumer products This product is regulated as a Carburetor Cleaner. This product is not compliant to be sold for use

in California, Connecticut, Delaware, Maryland, New Hampshire, Rhode Island, and the following counties in Utah: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber. This product is

compliant in all other states.

 VOC content (CA)
 36.4 %

 VOC content (OTC)
 36.4 %

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Philippines

Philippine Inventory of Chemicals and Chemical Substances

No

Philippine inventory of Chemicals and Chemical Substances

(PICCS)

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

### 16. Other information, including date of preparation or last revision

Issue date 12-23-2019
Prepared by Allison Yoon

Version # 01

Further information CRC # 684/1002726

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

SDS US

professional, or CRC Industries, Inc..

Revision information Composition / Information on Ingredients: Disclosure Overrides

Handling and storage: Precautions for safe handling

Handling and storage: Conditions for safe storage, including any incompatibilities

Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information

Regulatory information: Consumer products

**GHS:** Classification

Material name: Engine Tune-Up & Decarbonizer - 13 oz

No. 06121 (Item# 1003919) Version #: 01 Issue date: 12-23-2019 11 / 11

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).