

SAFETY DATA SHEET

1. Identification

Product identifier Syn-Go® Multi-Grade Synthetic Gear Oil SAE 75W90

Other means of identification

Product Code No. SL2482 (Item# 1007821)

Recommended use Multi-grade synthetic gear oil

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

885 Louis Dr. Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Contaminated work clothing

Category 1A

must not be allowed out of the workplace. Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

otherwise None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy paraffinic	d	64742-54-7	20 - 30
distillates (petroleum), hydrotreated light paraffinic	d	64742-55-8	20 - 30
poly long-chain alkyl methacrylate		Proprietary	1 - 3
long-chain alkyl amine		Proprietary	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantMay cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. **media**

Specific hazards arising from During fire, gases hazardous to health may be formed. **the chemical**

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for The product is immiscible with water and will spread on the water surface. containment and cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilitiesStore in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Oc

cupational exposure limits			
U.S OSHA Components	Туре	Value	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for Air C Components	Contaminants (29 CFR 1910.1000) Type	Value	Form
distillates (petroleum),	PEL	5 mg/m3	Mist.
hydrotreated heavy paraffinic (CAS 64742-54-7)	FEL	5 mg/ms	iviist.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
ACGIH Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values	TWA	5 mg/m3	Inhalable fraction
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			_
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
,	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Chemi			F
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
· · · · · · · · · · · · · · · · · · ·	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light paraffinic	STEL	10 mg/m3	Mist.

Biological limit values

(CAS 64742-55-8)

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

5 mg/m3

Mist.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

TWA

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. Liquid. **Form** Color Yellow.

Odor Mild petroleum. **Odor threshold** Not available. Ha Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

485 °F (251.7 °C) estimated

range

348 °F (175.6 °C) Tag Closed Cup Flash point

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

1 hPa estimated Vapor pressure > 1 (air = 1)Vapor density Relative density 0.87

Solubility(ies)

Solubility (water) Insoluble. Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available. Percent volatile 58.8 % estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Nitrogen oxides (NOx). Sulfur oxides. Phosphorous oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard. **Symptoms related to the**May cause an allergic skin reaction. Dermatitis. Rash.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

long-chain alkyl amine

<u>Acute</u>

Dermal

LD50 Rabbit 251 mg/kg

Oral

LD50 Rat 612 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Aquatic Acute

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Material name: Syn-Go® Multi-Grade Synthetic Gear Oil SAE 75W90 No. SL2482 (Item# 1007821) Version #: 01 Issue date: 12-14-2017

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Acute toxicity (any route of exposure)
categories Respiratory or skin sensitization

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Massachusetts RTK - Substance List

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. Pennsylvania Worker and Community Right-to-Know Law

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

California Proposition 65



WARNING: This product can expose you to chemicals including ethylene oxide, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

 1,4-dioxane (CAS 123-91-1)
 Listed: January 1, 1988

 ethyl acrylate (CAS 140-88-5)
 Listed: July 1, 1989

 ethylene oxide (CAS 75-21-8)
 Listed: July 1, 1987

 propylene oxide (CAS 75-56-9)
 Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR Not determined

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Taiwan

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Toxic Chemical Substances (TCS)

Yes

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

12-14-2017 Issue date Allison Yoon Prepared by

Version # 01

Further information CRC # 783/1002795

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

NFPA ratings



The information contained in this document applies to this specific material as supplied. It may not Disclaimer

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

Material name: Syn-Go® Multi-Grade Synthetic Gear Oil SAE 75W90 No. SL2482 (Item# 1007821) Version #: 01 Issue date: 12-14-2017