



1. Identification

Product identifier	Parts Cleaner & Degreaser - 1 lb 2 oz			
Other means of identification				
Product Code	Item# 1751863			
Recommended use	General purpose degreaser			
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier	/Distributor information			
Manufactured or sold by:				
Company name	CRC Industries, Inc.			
Address	885 Louis Dr.			
	Warminster, PA 18974 US			
Telephone				
General Information	215-674-4300			
Technical Assistance	800-521-3168			
Customer Service	800-272-4620			
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)			
Website	www.crcindustries.com			

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.

Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
methyl acetate		79-20-9	40 - 50
acetone		67-64-1	10 - 20
octamethylcyclotetrasiloxane		556-67-2	10 - 20
carbon dioxide		124-38-9	5 - 10
naphtha (petroleum), hydrotreated light		64742-49-0	5 - 10
heptane, branched, cyclic and linear		426260-76-6	1 - 3
n-heptane		142-82-5	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.	
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 2 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
methyl acetate (CAS 79-20-9)	PEL	610 mg/m3	
		200 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Туре	Value	alue	
acetone (CAS 67-64-1)	STEL	500 ppm		
	TWA	250 ppm		
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm		
	TWA	5000 ppm		
methyl acetate (CAS 79-20-9)	STEL	250 ppm		
	TWA	200 ppm		
n-heptane (CAS 142-82-5)	STEL	500 ppm		
	TWA	400 ppm		
US. NIOSH: Pocket Guide to Chen	nical Hazards			
Components	Туре	Value		
acetone (CAS 67-64-1)	TWA	590 mg/m3		
		250 ppm		
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3		
		30000 ppm		
	TWA	9000 mg/m3		
		5000 ppm		
methyl acetate (CAS 79-20-9)	STEL	760 mg/m3		
		250 ppm		
	TWA	610 mg/m3		
		200 ppm		
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3		
/		100 ppm		
n-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3		
	-	440 ppm		
		••		
	TWA	350 mg/m3		

US. Workplace Environmental Exposure Components		evel (WEEL) Guides Type Valu		ue	
octamethylcyclotetrasiloxa e (CAS 556-67-2)	an	TWA	10	ppm	
Biological limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, p	lease see the sourc	e document.			
Appropriate engineering controls	should be ma or other engin exposure limit	tched to conditions. If ap neering controls to mainta	plicable, use pro ain airborne level	nour) should be used. Ventilation rates cess enclosures, local exhaust ventilation, s below recommended exposure limits. If rborne levels to an acceptable level. Provide	
Individual protection measu	res, such as perso	nal protective equipme	ent		
Eye/face protection	Wear safety g	lasses with side shields	(or goggles).		
Skin protection					
Hand protection	Wear protecti	ve gloves such as: Nitrile	e. Polyvinyl alcoh	ol (PVA). Viton/butyl.	
Other	Wear appropr	Wear appropriate chemical resistant clothing.			
Respiratory protection	NIOSH-appro breathing app	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.			
Thermal hazards	Wear appropr	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	personal hygi	ene measures, such as v or smoking. Routinely w	washing after har	using do not smoke. Always observe good ndling the material and before eating, g and protective equipment to remove	

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Mild solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-138.5 °F (-94.7 °C) estimated
Initial boiling point and boiling range	133 °F (56.1 °C) estimated
Flash point	< 0 °F (< -17.8 °C) Setaflash
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.8 % estimated
Flammability limit - upper (%)	16.9 % estimated
Vapor pressure	923.3 hPa estimated
Vapor density	> 2 (air = 1)
Relative density	0.89 estimated
Solubility(ies)	
Solubility (water)	Slightly soluble.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	539.6 °F (282 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	81.9 % estimated

10. Stability and reactivityReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardous
reactionsNo dangerous reaction known under conditions of normal use.Conditions to avoidHeat, flames and sparks. Contact with incompatible materials.Incompatible materialsStrong oxidizing agents. Strong acids. Strong bases. Aldehydes. Alkalies. Amines. Ammonia.
Peroxides.

Hazardous decomposition Carbon oxides. Formaldehyde. products

·

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.	
Components	Species	Test Results
acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg
Oral		
LD50	Rat	5800 mg/kg
heptane, branched, cyclic and line	ear (CAS 426260-76-6)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 60 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity	cinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
	IARC Monographs. Overall Evaluation of Carcinogenicity			
Not listed. OSHA Specifically Regulate	ed Substances ((29 CFR 1910.1001-1053)		
Not listed.				
US. National Toxicology Pro	ogram (NTP) Re	eport on Carcinogens		
Not listed. Reproductive toxicity	Suspected of	damaging fertility.		
Specific target organ toxicity -	-			
single exposure		May cause drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure		Not classified.		
Aspiration hazard	-	swallowed and enters airways.		
Chronic effects	Prolonged inh	alation may be harmful.		
12. Ecological information	n			
Ecotoxicity	Toxic to aquat	tic life with long lasting effects.		
Components		Species	Test Results	
acetone (CAS 67-64-1)		•		
Aquatic				
-	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Acute		Danhnia magna	10204 17704 mg/L 48 hours	
Crustacea	EC50	Daphnia magna	10294 - 17704 mg/l, 48 hours	
heptane, branched, cyclic and	linear (CAS 42	6260-76-6)		
Aquatic Acute				
Crustacea	EC50	Water flea (Daphnia magna)	1.5 mg/l, 48 hours	
methyl acetate (CAS 79-20-9)		······································		
Aquatic	/			
•	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours	
naphtha (petroleum), hydrotre Aquatic <i>Acute</i>	eated light (CAS	,		
Crustacea	EC50	Daphnia	1 - 10 mg/l, 48 hours	
Fish	LC50	Fish	1 - 10 mg/l, 96 hours	
n-heptane (CAS 142-82-5) Aquatic Acute				
Crustacea	EC50	Water flea (Daphnia magna)	1.5 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	2.1 - 2.98 mg/l, 96 hours	
Persistence and degradability	No data is ava	ailable on the degradability of any ingredier	its in the mixture.	
Bioaccumulative potential		5 , 5		
Partition coefficient n-octan acetone	ol / water (log l	-0.24		
methyl acetate n-heptane		0.18 4.66		
Bioconcentration factor (BC	CF)	1.00		
naphtha (petroleum), hydrotre		10 - 25000		
octamethylcyclotetrasiloxane	NI- L C	Result: 12400		
Mobility in soil	No data availa			
Other adverse effects	The product c potential.	ontains volatile organic compounds which l	nave a photochemical ozone creation	


13. Disposal considerations

Disposal instructions	If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT		
U	N number	UN1950
UI	N proper shipping name	Aerosols, flammable, Limited Quantity
Tr	ansport hazard class(es)	
	Class	2.1
	Subsidiary risk	
Pa	acking group	Not applicable.
	nvironmental hazards	
	Marine pollutant	Yes, but exempt from the regulations.
S	pecial precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	pecial provisions	N82
	ackaging exceptions	306
	ackaging non bulk	304
Pa	ackaging bulk	None
ΙΑΤΑ		
UI	N number	UN1950
UI	N proper shipping name	Aerosols, flammable, Limited Quantity
Tr	ansport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
Pa	acking group	Not applicable.
EF	RG Code	10L
S	pecial precautions for user	Read safety instructions, SDS and emergency procedures before handling.
O	ther information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
IMDG		
•	N number	UN1950
	N proper shipping name	AEROSOLS, Limited Quantity
Tr	ansport hazard class(es)	
	Class	2.1
_	Subsidiary risk	-
	acking group	Not applicable.
Er	nvironmental hazards	
	Marine pollutant	Yes, but exempt from the regulations.
	mS	F-D, S-U
S	pecial precautions for user	Read safety instructions, SDS and emergency procedures before handling.







15. Regulatory information

0)		
US federal regulations	This product is a "Hazardous Standard, 29 CFR 1910.1200	Chemical" as defined by the OSHA Hazard Communication
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)		
octamethylcyclotetrasiloxane (CAS 556-67-2) SARA 304 Emergency release notification		1.0 % One-Time Export Notification only.
Not regulated.		
OSHA Specifically Regu Not listed.	lated Substances (29 CFR 19	10.1001-1053)
CERCLA Hazardous Su	bstance List (40 CFR 302.4)	
acetone (CAS 67-64 methyl acetate (CAS	79-20-9)	
CERCLA Hazardous Su	bstances: Reportable quantity	1
acetone (CAS 67-64 methyl acetate (CAS		5000 LBS 100 LBS
Spills or releases resultin Response Center (800-42	g in the loss of any ingredient at 24-8802) and to your Local Eme	or above its RQ require immediate notification to the National rgency Planning Committee.
Other federal regulations		
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants	s (HAPs) List
Not regulated.	112(r) Accidental Release Pro	
Not regulated.	()	
Safe Drinking Water Act (SDWA)	Not regulated.	
Drug Enforcement Adm Chemical Code Number		ntial Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and
acetone (CAS 67-64	-1)	6532
		xempt Chemical Mixtures (21 CFR 1310.12(c))
acetone (CAS 67-64-	-1)	35 %WV
DEA Exempt Chemical	,	
acetone (CAS 67-64-	-1)	6532
	,	fety in the Flavor Manufacturing Workplace
acetone (CAS 67-64-	-1)	Low priority
methyl acetate (CAS	79-20-9)	Low priority
Food and Drug Administration (FDA)	Not regulated.	
Superfund Amendments and Re	authorization Act of 1986 (SA	RA)
Classified hazard	Flammable (gases, aerosols, Gas under pressure	-
categories	Serious eye damage or eye in	ritation
	Reproductive toxicity	aingle or repeated expensive)
	Specific target organ toxicity (Aspiration hazard	single of repeated exposure
	Hazard not otherwise classifie	d (HNOC)
SARA 302 Extremely hazard	lous substance	

Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting) Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Massachusetts RTK - Substance List

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Rhode Island RTK

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 benzene (CAS 71-43-2) Listed: February 27, 1987 cumene (CAS 98-82-8) Listed: April 6, 2010 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 lead (CAS 7439-92-1) Listed: October 1, 1992 naphthalene (CAS 91-20-3) Listed: April 19, 2002 California Proposition 65 - CRT: Listed date/Developmental toxin benzene (CAS 71-43-2) Listed: December 26, 1997 lead (CAS 7439-92-1) Listed: February 27, 1987 methanol (CAS 67-56-1) Listed: March 16, 2012 toluene (CAS 108-88-3) Listed: January 1, 1991 California Proposition 65 - CRT: Listed date/Female reproductive toxin lead (CAS 7439-92-1) Listed: February 27, 1987 California Proposition 65 - CRT: Listed date/Male reproductive toxin benzene (CAS 71-43-2) Listed: December 26, 1997 lead (CAS 7439-92-1) Listed: February 27, 1987

n-hexane (CAS 110-54-3) US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) acetone (CAS 67-64-1)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) octamethylcyclotetrasiloxane (CAS 556-67-2)

Volatile organic compounds (VO	C) regulations	
EPA		
VOC content (40 CFR 51.100(s))	9.5 %	
Consumer products (40 CFR 59, Subpt. C)	Not regulated	
State		
Consumer products	This product is regulated as a General Purpose Degreaser (aerosol). use in all 50 states.	This product is compliant for
VOC content (CA)	9.5 %	
VOC content (OTC)	9.5 %	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	and a fair is an dealer and the state is an advector of a second second second second by the state of the state	······

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-03-2020
Prepared by	Dustin Kern
Version #	01
Further information	CRC # 1752013
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc