



# DRILLER RED

## Driller Red Grease

With an industry high 80+ lb Timken OK Load, **CRC Driller Red Grease** is designed to withstand greater amounts of pressure, especially in oil and gas applications. Driller Red Grease offers superior wear and shock load protection to applications with high axial or thrust loads.

### Benefits:

- ▶ Premium quality lithium complex, Extreme Pressure (EP) grease
- ▶ Outstanding protection in wet environments; water washout <3%
- ▶ “Tacky”, stay in place formula makes it excellent for drilling applications
- ▶ Long lasting lubricating protection for Plug, Gate and Ball valves where an integral sealing and corrosion preventative film is required; ensures a smooth controlled actuation over extended maintenance periods
- ▶ High compatible thickener base reduces equipment failure risk during conversion break-in process
- ▶ The distinctive red color makes it easy to identify during and after lubrication
- ▶ Superior protection to lubricate a wide variety of severe duty automotive, trucking, industrial, mining and construction equipment

**80+ lb Timken OK Load**



Made in USA



Your Best Solution™

Customer Service: 800-272-4620  
 Technical Assistance: 800-521-3168  
[www.crcindustries.com/ei](http://www.crcindustries.com/ei)



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Manyate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.

©2014 CRC Industries, Inc.

I0389-PDF



## Driller Red Grease

**CRC Driller Red Grease** eliminates the need to inventory other greases, as it may be used in wheel bearings, ball joints, U-joints, chassis, fifth wheels, king pins, as well as industrial bearings, couplings and gears.

CRC Part #	Container Size	Base Type	NLGI Rating
SL3640	14 oz cartridge	Lithium complex	#2
SL3650	35 lb pail	Lithium complex	#2

Typical Characteristics	
NLGI Consistency Number	2
Thickener Lithium	Complex
Texture, Smooth	Tacky
Color, Observed	Red
Worked 60 Penetration, D-217	265-295
Dropping Point, D-566, °F (°C)	550 (288)
Wheel Bearing Leakage, D-4290, g loss	2.0
Timken EP Text, OK Load, lbs	80+
Water Washout, D-1264, % loss	2.5 @ 175°F
Rust Prevention, D-1743, rating	Pass
Oil Separation, D-1742, % loss	1.0
Four-Ball Wear, D2266, mm	0.45
Four-Ball EP Weld Point, D-2596, kgf	315
Four-Ball Load Wear Index, D-2596, kgf	50



Your Best Solution™

Customer Service: 800-272-4620  
 Technical Assistance: 800-521-3168  
[www.crcindustries.com/ei](http://www.crcindustries.com/ei)



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.

©2014 CRC Industries, Inc.